# XANTÉ

## INTRODUCING! X-16™ UV PRINTER

**Prints up to 18”x24”!**

## PRINT ON VIRTUALLY ANY MEDIA!

- CMYK + WW
- UP TO 2880 DPI RESOLUTION
- PRINT ON MEDIA UP TO 7.75 INCHES TALL
- SINGLE LED LAMPS
  (Instant Ink Curing)

Adobe® PDF

iQueue WORKFLOW

US: 251.473.6502
EU: +31 (0) 26.319.3210
xante.com

# BEST. EVER.

**The X-UV Printer cannot be beat.**

*Large flatbed printers designed for signage and graphics print at high speeds but are limited by substrate thickness.*
*Small format printers designed for specialty items print at slower speeds and are limited by substrate length and width.*

*The Xanté family of X-UV Printers do **BOTH**.*
*It's the best of both worlds.*

***CONTACT US TODAY FOR MORE INFORMATION.***

# PRINT IN THE SWEET SPOT

POWERED BY iQueue

*Simply Brilliant Color Workflow*

# INCLUDED!

## *FIVE WAYS TO PRINT INTENSE, BRILLIANT, PURE WHITE.*

Flood, White Active Pixels, White Inactive Pixels, White Spot Color, or No White

## *BUILD DEPTH WITH LAYERS OF FAST-DRYING, UV-CURED INK.*

Create impressive displays that grab attention or communicate important information in braille. This process is fast and renders strong, durable results.

**251.473.6502**

## *Signage • Manufacturing • Specialty Items • Industrial • Packaging*

# PRINT FAST.
# PRINT TALL.

MONTROS CORPORATION



***HIGH QUALITY SIGNAGE AT SPEEDS OVER 100 sq.ft./hour***

*Resolution - up to 2880 dpi*
*Media size - 18” x 24” x 7.75”*
*Media weight - up to 22 pounds!*

VOTE
XANTÉ
THE X-16
BEST UV PRINTER!

## BEST-IN-CLASS

**XANTÉ.com**

All content including X-16® is trademark Xanté Corporation. 2020. All Rights Reserved.

# X-16 SPECIFICATIONS

## PRINTING CAPABILITIES

| | |
|---|---|
| **Max. print size:** | 24” x 18” (60.9cm x 45.7cm) |
| **Min. print size:** | .5” x .5” |
| **Max. print height:** | 7.75” ( 19.68cm) |
| **Media transport:** | 24” x 19.7” (60.9cm x 50cm)<br>Vacuum bed |
| **Print colors:** | CMYK + WW |
| **Resolution:** | 720/1080/1440/2160/2880 DPI Resolutions |
| **UV lamp:** | Single LED, 385-415 nM, low heat curing lamps |

## INK AND MEDIA

| | |
|---|---|
| **Ink type:** | UV, 1 liter bottles per color |
| **Media types:** | PVC plastic, styrene, wood, aluminum, metal, acrylics, coroplast, ceramics, fabric, leather, composites, paperboard, foamboard, glass, carpet, tile and more |

## PRINTER CONNECTIVITY

1-Gigabit Ethernet

## PREPRESS SOFTWARE

**Xanté iQueue Workflow:** Adobe® PostScript® 3™, Independent CMYK Density Control, Spot Color Matching, Imposition, Digital File Editing, Variable Printing, and much more

## WEIGHTS, DIMENSIONS

| | |
|---|---|
| **Dimensions:** | 28”L X 55”W X 32”H (71 x 139 x 81cm) |
| **Net/Gross weight:** | 255lbs (115kg) |
| **Power supply:** | 110v or 220v 50-60hz |

## WORKING CONDITION

| | |
|---|---|
| **Operating temperature:** | 22-26°C (68°F - 78°F) |
| Relative humidity: | 35-75RH |

Adobe® PostScript® 3™

XANTÉ

**US:** 251.473.6502
**EU:** +31 (0) 26.319.3210
xante.com

**iQueue Simply Brilliant Workflow (Included)**

Digital Color Workflow with Advanced Color Matching and File Management Tools

©2020 Xanté Corporation. Xanté, the Xanté logo, iQueue, RightON and X-16 are registered trademarks of Xanté Corporation.
Adobe® and PostScript® are registered trademarks of Adobe Systems, Inc. All rights reserved.

03.10.2020